



Cisco

642-655

WAASFE-Wide Area Application Services for Field Engineers

- A. Traffic classifiers
- B. Application definitions
- C. Policy maps
- D. Baseline policies

Answer: C

Question: 59

What can be displayed by the command show wccp services?

- A. The WCCP service groups that are configured on the router
- B. The routers that are registered with the WCCP service of the WAE
- C. The WAE appliances that are registered with the router WCCP service
- D. The WCCP service groups that are configured on the WAE

Answer: D

Question: 60

A WAE device recently registered against a Central Manager. What must you do before the WAE can receive a policy and interact with other WAE devices?

- A. Specify a primary interface.
- B. Assign an IP address.
- C. Specify the device group.
- D. Activate the device.

Answer: D

Question: 61

In a WAAS Application Traffic Policy, which three match conditions are valid for traffic classifiers? (Choose three.)

- A. IP address
- B. Routing
- C. Subnet
- D. TCP port

Answer: A, C, D

Question: 62

The following diagram displays an entry from a TFO transaction log on the WAE. What conclusion can be drawn from this result?

```
waas-edge-1# type-tail working.log
...
Wed Jan 3 07:42:09 2007:BP:10.10.10.10:443:10.10.100.2:60107:NO_PEER: OPT:
```

- A. The connection is being optimized correctly, but no traffic has been optimized yet.
- B. The connection is not being optimized because the remote WAE had different TFO optimizations configured than the local WAE.
- C. The connection is not being optimized because autodiscovery failed with the remote WAE.
- D. The connection is not being optimized because the configured optimizations are not supported on the peer WAE.

Answer: C

Question: 63

Which command verifies that a WAE in-line card is intercepting traffic from the correct VLANs?

- A. show wccp services
- B. show ip access-lists
- C. show int inlinegroup x/y
- D. show wccp vlans inline

Answer: C

Question: 64

Cisco WAAS is a powerful application acceleration and WAN optimization solution that accelerates the performance of any TCP-based application delivered across a WAN. A WAAS mobile user is experiencing poor performance that is not experienced when WAAS mobile is disabled. What is the first troubleshooting step?

- A. Turn off the WAAS mobile server and run applications natively.
- B. Turn off the WAAS mobile client.
- C. Turn on the WAAS mobile client.
- D. Generate a system report while the network performance is occurring.

Answer: D

Question: 65

Which feature of Central Manager specifies the configuration items that a user can see?

- A. Roles
- B. Policy maps
- C. System settings
- D. Authentication providers

Answer: A

Question: 66

When configuring adapter policies in a Cisco WAAS environment, what is the purpose of the EPM adapter?

- A. To specify the traffic that is associated with an optimization
- B. To provide grouping for statistics and monitoring
- C. To differentiate priority on a congested link
- D. To identify the dynamically assigned port number of a connection

Answer: D

Question: 67

Which three must be configured on the edge WAE when you configure an edge print queue? (Choose three.)

- A. Central Manager service
- B. Device URI
- C. Print administration user
- D. WAFS edge service

Answer: B, C, D

Question: 68

Which two options are available for Cisco WAAS file-services integration? (Choose two.)

- A. Nontransparent appearing as a node on the remote office LAN
- B. Transparent appearing as a node on the remote office LAN
- C. Nontransparent not appearing as a node on the remote office LAN
- D. Transparent not appearing as a node on the remote office LAN

Answer: A, D

Question: 69

Which Cisco WAAS feature is used to provide a logical grouping of traffic types to support the monitoring and collection of statistics?

- A. Application definitions
- B. Baseline policies
- C. Policy maps
- D. Traffic classifiers

Answer: A

Question: 70

Which three must be configured when you configure an edge print queue? (Choose three.)

- A. Device URI
- B. EPM policy
- C. Printer name
- D. Wafs edge service

Answer: A, C, D

Question: 71

What is a valid Cisco WAAS device group type?

- A. Location group
- B. WAFS core cluster
- C. Application accelerator group
- D. Authentication group

Answer: B

Download Full Version From <https://www.certkillers.net>



DON'T KNOW
OR NO PREFERENCE

Pass your exam at First Attempt....Guaranteed!